

CURLOPT_FNMATCH_FUNCTION(3) curl_easy_setopt options CURLOPT_FNMATCH_FUNCTION(3)

NAME

CURLOPT_FNMATCH_FUNCTION – wildcard matching function callback

SYNOPSIS

```
#include <curl/curl.h>
```

```
int fnmatch_callback(void *ptr,  
                    const char *pattern,  
                    const char *string);
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FNMATCH_FUNCTION,  
                          fnmatch_callback);
```

DESCRIPTION

Pass a pointer to your callback function, which should match the prototype shown above.

This callback s used for wildcard matching.

Return *CURL_FNMATCHFUNC_MATCH* if pattern matches the string, *CURL_FNMATCHFUNC_NOMATCH* if not or *CURL_FNMATCHFUNC_FAIL* if an error occurred.

DEFAULT

NULL == an internal function for wildcard matching.

PROTOCOLS

FTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.21.0

RETURN VALUE

Returns CURLE_OK if the option is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_FNMATCH_DATA(3), CURLOPT_DEBUGFUNCTION(3),