

CURLOPT\_PROXY\_TRANSFER\_MODE(3)curl\_easy\_setopt optionsCURLOPT\_PROXY\_TRANSFER\_MODE(3)

## NAME

CURLOPT\_PROXY\_TRANSFER\_MODE – append FTP transfer mode to URL for proxy

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_PROXY_TRANSFER_MODE, long enabled);
```

## DESCRIPTION

Pass a long. If the value is set to 1 (one), it tells libcurl to set the transfer mode (binary or ASCII) for FTP transfers done via a HTTP proxy, by appending ;type=a or ;type=i to the URL. Without this setting, or it being set to 0 (zero, the default), *CURLOPT\_TRANSFERTEXT(3)* has no effect when doing FTP via a proxy. Beware that not all proxies support this feature.

## DEFAULT

0, disabled

## PROTOCOLS

FTP over proxy

## EXAMPLE

TODO

## AVAILABILITY

Added in 7.18.0

## RETURN VALUE

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if the enabled value is not supported.

## SEE ALSO

*CURLOPT\_PROXY(3)*, *CURLOPT\_HTTPPROXYTUNNEL(3)*,